



Cat6A shielded 24 port panel flat, with individual shielded keystone jacks OR-PHDTKS6A24

OVERVIEW

24 port Cat6A shielded flat panel with 24 rear loading TKS6A shielded jacks. Includes rear cable management, and grounding lug. Occupies 1 rack unit of space 1.75" x 19"

FEATURES

- **Meets Category 6A component standard:** Ensures standards compliance
- **Easy lace wiring** Reduces wiring time
- **Easy to follow universal wiring label:** Quick and user-friendly, eliminates confusion
- **Rear loading:** preferred mounting for panels
- **Supplied rear cable management :** supports good cabling practices.
- **RoHS compliant:** Lead free

Dimension Info

Depth Metric: 152.4 mm
Depth U S: 6.0 in
Width Metric: 482.6 mm
Rack Units: 1
Width U S: 19.00"
Height U S: 1.72 in

General Info

Type: Patch Panels
Category Performance Application: Category 6A shielded
Footprint: Keystone
Mod Jack Wiring: Universal T568A/B
Color: Black & silver
Number Of Ports: 24
Termination: Insulation displacement contacts

Technical Info

Category Rating: Cat 6a component compliant
Performance Rating: Cat6a

Listing Agency Info

FCC

Eco Information

RoHS Compliant: Yes

