

700TVL VANDAL RESISTANT TRUE DAY/NIGHT DOME



Feature	XVD28V12DNIR700
Housing	Die-cast Aluminium (Vandal Resistant)
Bubble	Polycarbonate
IP Rating	IP66
Sensor	1/3" 760H CCD
Video Format	PAL
Resolution	700TVL
Min Illumination	0 Lux (IR ON), 0.5 lux colour
IR illumination range	Upto 20m
S/N ratio	50dB (AGC off)
Lens	2.8-12mm IR corrected Direct drive
AGC options	Auto: manual
BLC options	On / off / HLC
Shutter	1/50th – 1/100000th
Mirror	On / Off
Colour Temp range	2200K – 10000K
Day / Night Mode	Automatic
DWDR	On / Off
Motion Detection	On / Off (Icon displayed on screen)
Privacy zone	On / Off 4 zones
Text	On / Off 15 characters
Sync Mode	Internal
Power	DC12V / AC24V
Current	Max 550mA
Operating temp	-10°C ~ 50°C
Storage Temperature	-20°C ~ 50°C
Dimensions	147mm (Dia) by 117mm (High)
Weight	1Kg

- True Day/Night operation – removable IR cut filter
- Ultra High 700TVL resolution
- Externally rated IP66
- IR illumination option (20m range)
- 2.8-12mm IR corrected lens
- Motion Detection on screen display