

700TVL VANDAL RESISTANT COLOUR/MONO DOME



Feature	XVD28V12CM700
Housing	Die-cast Aluminium (Vandal Resistant)
Bubble	Polycarbonate
IP Rating	IP65
Sensor	1/3" 760H CCD
Video Format	PAL
Resolution	700TVL
Min Illumination	0.01 Lux
S/N ratio	50dB (AGC off)
Lens	2.8-12mm IR corrected Direct drive
AGC options	Auto: manual
BLC options	On / off / HLC
Shutter	1/50th – 1/100000th
Mirror	On / Off
Colour Temp range	2200K – 10000K
Colour / Mono Mode	Automatic
DWDR	On / Off
Motion Detection	On / Off (Icon displayed on screen)
Privacy zone	On / Off 4 zones
Text	On / Off 15 characters
Sync Mode	Internal
Power	DC12V / AC24V
Current	Max 150mA
Operating temp	-10°C ~ 50°C
Storage Temperature	-20°C ~ 50°C
Dimensions	147mm (Dia) by 117mm (High)
Weight	1Kg

- **Colour / Mono operation – (non IR sensitive)**
- **700TVL resolution**
- **Externally rated IP65**
- **2.8-12mm IR corrected lens**
- **Motion Detection on screen display**