

Sentry Smart CDU

Key Features

- > **High Density:** Single-power input feed; 24 outlets per enclosure (Qty 18 IEC C13 & 6 IEC C19 outlets)
- > **Power Distribution:** 208-240V, 20A and 30A; 230V 16A and 32A power input feed options
- > **Input Current Monitor:** Precisely measure the aggregate current draw (in amps) of the circuit. On-site verification of the input current with LED digital display. Remote verification via web browser or serial screen.
- > **IP Access & Security:** Web interface, SSL, SSH, Telnet, SNMP, FTP, SNTp, Syslog, LDAP, LDAPS, TACACS, RADIUS, and RS-232 access
- > **SNMP Traps and Email alerts:** Provide automated alerts for power and environmental conditions
- > **Environmental Monitoring:** Each Smart CDU supports two external temperature & humidity probes and reports conditions thru the user interface without the need for additional IP addresses
- > **Add an Expansion Module:** Connect the Smart Expansion CDU (CLG) to a Master unit (CSG) for power monitoring of separate power circuits from a single IP address

CSG-24V2/E Smart POPS™ CDU with Mixed Outlets

High-Density Power Distribution

The Smart Cabinet Power Distribution Units (CDU) provide reliable power distribution combined with local and remote power monitoring and environmental monitoring via IP. Use the network interface to view power, temperature and humidity levels via Web browser, or receive SNMP-based alarms and email alerts when conditions exceed defined thresholds.

Sentry POPS (Per Outlet Power Sensing) combines all of the features and functions of a Smart CDU with the ability to provide power monitoring per an individual outlet/device. Power information per individual outlet/device includes current, voltage, power (kW), apparent power, crest factor, and power factor. Using out grouping technology, power information is available per device, groups of devices (application), individual CDU or cabinet.

Additional Benefits:



POPS™ (Per Outlet Power Sensing)

Monitor Current Load (A), Voltage (V), Power (W), Apparent Power (VA), Crest Factor and Power Factor per outlet at an accuracy of $\pm 2\%$.



Branch Circuit Protection

The Sentry CDU Family meets the UL 60950-1 requirement for Branch Circuit Protections
> UL-489 rated circuit breakers



PIPS - Per Input Power Sensing

Accurately measures Active Power, Apparent Power, Energy k-Wh, Power Capacity, and Power Capacity Used using the network interface. See the aggregate current draw, in Amps, locally using the onboard LED.



Temperature and Humidity

The Smart CDU supports two external 10ft (3m) probes. Each of these probes measure both temperature and humidity. Receive SNMP-based alerts or email notifications when conditions exceed defined thresholds.



Mixed Outlets

This Smart CDU combines 18 IEC 60320 C13 and 6 IEC 60320 C19 outlets within a single CDU to monitor power at the outlet-level.



Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)
CSG-24V2A415A1 CLG-24V2A415A1 *	200-240V 50/60Hz	20A	IEC C20 Inlet, Bottom/Frt Entry	(18) IEC 60320/C13 (6) IEC 60320/C19	61.0 x 1.75 x 3.50 in. (1550 x 44 x 89 mm)
CSG-24V2C415A1 CLG-24V2C415A1 *	200-240V 50/60Hz	30A	NEMA L6-30P Plug, 10'(3m), Bottom/Frt Cord	(18) IEC 60320/C13 (6) IEC 60320/C19	61.0 x 1.75 x 3.50 in. (1550 x 44 x 89 mm)
CSG-24VEA415A1 CLG-24VEA415A1 *	230V 50/60Hz	16A	IEC C20 Inlet, Bottom/Frt Entry	(18) IEC 60320/C13 (6) IEC 60320/C19	61.0 x 1.75 x 3.50 in. (1550 x 44 x 89 mm)
CSG-24VEK415A1 CLG-24VEK415A1 *	230V 50/60Hz	32A	IEC Blue 2P+G Plug, 10'(3m), Bottom/Frt Cord	(18) IEC 60320/C13 (6) IEC 60320/C19	61.0 x 1.75 x 3.50 in. (1550 x 44 x 89 mm)

Additional Features and Specifications

Agency Approvals

- > US & Canada (cTUVus mark) to UL 60950-1:2003 and CAN/CSA 22.2 No. 60950-1-03
- > European Union (TUVGS mark) to EN 60950-1:2001
- > FCC Class A, Part 15
- > CE
- > EMC to EN 55022 Class A, EN 55024, CISPR 22 Class A

Communications and Security

- > 10/100 BaseT Ethernet
- > HTTP/HTTPS 55(A),37(P)59.9V

Branch Circuit Protection

- > Compliant to UL 60950-1



Server Technology

HEADQUARTERS - NORTH AMERICA
 Server Technology, Inc.
 1040 Sandhill Drive
 Reno, NV 89521
 United States
 1.775.284.2000 Tel
 1.775.284.2065 Fax
 sales@servertech.com
 www.servertech.com
 www.servertechblog.com

EMEA
 Server Technology Intl
 Sienna Court
 The Broadway
 Maidenhead
 Berkshire
 SL6 1NJ
 United Kingdom
 +44 (0) 1628 509053 Tel
 +44 (0) 1628 509100 Fax
 salesintl@servertech.com

APAC
 Server Technology Intl
 37th Floor, Singapore Land Tower
 50 Raffles Place
 Singapore 048623
 +65 (0) 6829 7008 Tel
 +65 (0) 6234 4574 Fax
 salesintl@servertech.com