

Sentry Switched CDU

Key Features

> High Density:

Power Distribution:

Input Current Monitor:

Networked Power Management:

IP Access & Security:

SNMP Traps and Email alerts:

Environmental Monitoring:

Add an Expansion Module:

CWG-24V4 Switched POPS™ CDU with 18xC13 and 6xC19 with PIPS

The Switched CDU combines network configuration and management with power distribution, environmental monitoring and the ability to provide power monitoring per an individual outlet/device. Power information per outlet includes current, voltage, power (kW), apparent power (VA), crest factor and power factor. Reboot a single or dual-power server with one command. Receive SNMP or email-based alerts when power or environmental conditions exceed thresholds. Assign user specific access rights to designated outlets or groups.

This Switched CDU has top entry for network, serial & environmental connections combined with a bottom power cord entry. Current monitors are easily inverted via the web GUI or serial interface. This provides flexibility when connecting Switched CDU's to overhead power or busways.

Additional Benefits:



POPS™ (Per Outlet Power Sensing)

Monitor Current Load (A), Voltage (V), Power (W), Apparent Power (VA), Crest Factor and Power Factor per outlet at an accuracy of $\pm 2\%$.



Branch Circuit Protection

The Sentry CDU Family meets the UL 60950-1 requirement for Branch Circuit Protections
> UL-489 rated circuit breakers





Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)
CWG-24V4J458A1 CXG-24V4J458A1	230/400V 3-Phase Wye, 50/60Hz	16A	IEC Red 6hr 3P+N+G Plug, 10'(3m), Top Cord Entry	(18) IEC 60320/C13 (6) IEC 60320/C19	1753 x 44 x 89 mm (69.0 x 1.75 x 3.50 in.)
CWG-24V4K458A1 CXG-24V4K458A1	230/400V 3-Phase Wye, 50/60Hz	32A	IEC Red 6hr 3P+N+G Plug, 10'(3m), Top Cord Entry	(18) IEC 60320/C13 (6) IEC 60320/C19	1753 x 44 x 89 mm (69.0 x 1.75 x 3.50 in.)



Server Technology

HEADQUARTERS - NORTH AMERICA
 Server Technology, Inc.
 1040 Sandhill Drive
 Reno, NV 89521
 United States
 1.775.284.2000 Tel
 1.775.284.2065 Fax
sales@servertech.com
www.servertech.com
www.servertechblog.com

EMEA
 Server Technology Intl
 Sienna Court
 The Broadway
 Maidenhead
 Berkshire
 SL6 1NJ
 United Kingdom
 +44 (0) 1628 509053 Tel
 +44 (0) 1628 509100 Fax
salesint@servertech.com

APAC
 Server Technology Intl
 37th Floor, Singapore Land Tower
 50 Raffles Place
 Singapore 048623
 +65 (0) 6829 7008 Tel
 +65 (0) 6234 4574 Fax
salesint@servertech.com