



Clarity Cat6a TracJack, T568A/B, 8 pos, Fog White 180 degree OR-TJ6A

OVERVIEW

Clarity 6A TracJack, ETL verified to TIA Category 6a component specification. Front-loading and front removable. Universal T568A/B wiring label and tapered wiring towers simplify termination. Tuned to Cat6a Clarity patch cords for optimum performance

FEATURES

- **ETL Verified to Category 6a component standard:** Ensures standards compliance.
- **Center tuned design:** Transparent interface with Clarity 6A/10G cords.
- **Easy lace IDC housing:** Reduces wiring time.
- **Easy to follow universal wiring label:** Quick and user-friendly, eliminates confusion.
- **Standard TracJack footprint:** Fits in all TracJack faceplates and housings.
- **Front removable:** Less intrusive access for adds, moves, changes.
- **Icon compatible, C6A marking on jack face:** Supports 606 designation requirements.

Dimension Info

Cable Diameter Range: 22-25 AWG
Depth Metric: 27.94 mm
Depth U S: 1.10"
Height Metric: 23.37 mm
Width Metric: 18.54 mm
Width U S: 0.73"
Height U S: 0.92"

General Info

Product Series: Clarity
Type: Jacks and Modules
Performance Category: Cat 6a component compliant
Footprint: TracJack
Mod Jack Wiring: Universal T568A/B
Color Cable Jacket: Yes
Color: Fog White

Technical Info

Wire Gauge: 22-25 AWG
Category Rating: Cat 6a component compliant
Performance Rating: Cat6a

Construction Info

Component2: Array of eight modular Quad Reactance Cat6a contacts - Material2: Beryllium copper, Finish_Plating2: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area
Component3: IDC contacts (Low noise) - Material3: Phosphor bronze, Finish_Plating3: Nickel plating with tin over plate

Listing Agency Info

FCC
UL E131600

Eco Information

RoHS Compliant: Yes

