


Sirocco Tubes (Internal)



Product description

Reduced fire hazard assemblies containing RFH tubes in an RFH sheath for blown fibre installations for in-building applications.

- Low friction internal coating for maximum fibre blowing distance.
- 5mm O/D, each tube accommodates up to a 12 fibre unit.
- LSOH indoor version with flame retardant properties, low smoke emission and containing no halogens.
- Individual tubes available in opaque or translucent material for fibre visibility.
- Choice of colours, can be customised to suit user requirements.
- Supplied on wooden drums. Each drum can contain either one continuous length of tube or multiple lengths for simultaneous installation.

Benefits

Simplified Planning

- Network is built according to today's needs.
- Fibre count can be increased as demand grows.

Cost Effective

- Pay as you grow – install empty tubes and only pay for fibre as and when required, spreading capital investment overtime.
- Reduced splicing – minimises branching and splicing of traditional networks thus reducing engineering costs.
- Continuous upgrade and repair of network with minimal installation cost and disruption.

Increased Flexibility

- Future proof network build.
- Networks are easily upgraded, branched or extended, giving maximum flexibility and uninterrupted fibre blowing right to the destination.
- Simplified emergency restoration.

Indoor Multi-Tube Bundles

Bundles of tubes bound in a LSOH outer sheath

- Available in 1, 2, 4, 7, 12, 19, 24 way (3 mm O/D available on request)

LSOH Low Smoke, Zero Halogen Sheath

- Fire retardant properties

© PRYSMIAN GROUP 2012, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alternation afterwards of product may give different results. The information claimed within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. This information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

Assembly Type	Product Code	Nominal O.D. (mm)	Ripcord Qty	Minimum Bend Radius (mm)	Max Tensile Strength (N)	Nominal Weight (g/m)	Drum Lengths (m)
1 way	IMR0501	5.0	-	150	80	14	500m D* 2000m R 1000m R* 4000m R
2 way	IMR0502	7.2 x 12.2	1	150	390	74	500m D 2000m R 1000m R 4000m R
4 way	IMR0504	12.2 x 12.2	1	250	600	118	500m D 2000m R 1000m R 4000m R
7 way	IMR0507	17.2	1	350	880	175	500m D 2000m R 1000m R 4000m R
12 way	IMR0512	22.5	2	450	1500	267	500m D 2000m R 1000m R 4000m R
19 way	IMR0519	27.2	2	550	2200	387	500m D 2000m R 1000m R 3500m R
24 way	IMR0524	31.7	2	640	2700	521	1000m D 2500m R 2000m R

D* Disposable drum R* Returnable drum

Material Compliance

- Flammability IEC 60332 Part 1 and Part 3
- Acid Gas Emission IEC 60754-1, max 0.5%
- No Halogen Content
- Temperature Index 270° C

Tensile

Tested in accordance with IEC 60794-1-2 Method E1. There shall be no permanent deformation of the primary or assembly parts after an applied load of 1.0 (spec. weight kg/km)N at 20mm/minute.

Crush Performance

Tested in accordance with IEC 60794-1-2 Method E3. After a maintained load of 400N for 1 minute there shall be no deformation of primary tubes greater than 0.5 mm.

Stress Crack Resistance

Tested in accordance with BS6469 Section 99.1 with chemical Caf on CF30.

© PRYSMIAN GROUP 2012, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alternation afterwards of product may give different results. The information claimed within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. This information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.