



# CAT5e UTP 1U 24 Port Rear Punch Patch Panel

## Key Features

- T-568B Wiring
- 19" Width 1U Height

## Panel Style:

Punch-Down

## Part No: TRI-000702

## General Description:

Cat5e rear LSA punchdown panel. 30-year link and/or channel warranty available when used with compatible Trident Data products.

## Relevant Standards:

ANSI/TIA/EIA-568. B.2-1

## Specification:

### Electrical

Voltage Rating	125 VAC RMS
Current Rating:	1.5AMP
Contact Resistance:	20 Milliohms Max
Insulation Resistance:	100 Megohms Min @ 500 VDC
Dielectric Strength:	750 VAC RMS 60Hz, 1min
C6 Permanent Link:	Conforms to ANSI/TIA/EIA-568. B.2-1

### Environmental

Storage:	-40°C to +70°C
Operation:	-10°C to +60°C

### Mechanical

Housing Material:	PBT +15%GF UL94V-0
Panel Frame:	S45C, Powder Coating in Black Colour
IDC Material:	PC, 110 UL94V-0 Contact: Phosphor Bronze, Tin Plated
RJ45 Jack Life:	750 times min
IDC Life:	200 times min
Wire:	AWG 22-24
TIA Cat6 Perm. Link Test:	Worst Pair NEXT margin > 3.0dB
Retentiveness of Insertion Structure:	50N 60+5s