

Features and technical specification

Part Number: VN/RED/1.5

Features:

- Fully self-contained automatic fire detection and extinguishing system.
- ‘Out of the box fire protection solution’ requiring no fire engineering design; quick and easy to install and simple to operate.
- Designed around EN54-2 C&IE design standards.
- LPCB approved Airsense HSSD detection for quick response.
- Novec1230 Extinguishing agent to cover 1.5 cubic meters.
- Approved and tested bottle & valve sets, specially designed performance tested discharge nozzles, proven fire tested performance.
- Volt free contacts for connection into 3rd party equipment.
- 19” rack mounted chassis.
- 2U (88mm) height.
- 479mm Depth



Technical Specification: Panel

Input Voltage	110/230VAC 50/60Hz via single fused IEC C13 socket
Output Voltage	110/230VAC 8A single IEC C14 socket
Output Switching	1 st stage fire alarm contacts form ‘C’ volt free contacts 2 nd stage alarm contacts form ‘C’ volt free contacts Common Fault form ‘C’ volt free contacts All output contact ratings - 8A @ 24V dc 24v dc output fused @ 500mA Fan/Air-conditioning power shutdown output (IEC). All wired outputs use Wiedmuller plug-in terminals.
Output data port	Extinguishant delay time 0,4,32,64,128 seconds
Remote Output	Extinguishant output
Remote Inputs	Extinguishant Release Hold off Release
Backup power	2 x 1.2 AH SLAB - 12hrs for standard Redetec unit
Operating Temperature	0 to +50°C
Operating Humidity	0 to 95% (non-condensing)
Power supply approvals	BS EN54-4 1998, EN55022 class B emissions limits & EN60950: 2000 safety standards
Power Supply Rating	1.5A PSU: 1.0A continuous load, 0.5A battery charge
Dimensions	19” (485mm) width, 2U (88mm) height, 479mm deep including nozzle suitable for 600mm cabinets, additional extension tubes supplied as standard for 800mm -1000mm+ cabinets.
Extinguishing type	1.2kgs (Novec 1230 1, 1, 1, 2, 2, 4, 5, 5, 5 –Nonfluoro-4-(Trifluoromethyl-3-Pentatone))
Fire detector type	1pcs Airsense Micra25 for High Sensitivity Smoke Detection (HSSD)
Shipping dimensions	190mm x 570mm x 590mm
Shipping weight	14.5kg



Protect your business with Redetec...

putting fire protection where it counts.

19” rack-mount fire protection solutions

t: 0161 874 1942 - f: 0161 872 3282 – email: sales@redetec.co.uk – web: www.redetec.co.uk
registered office: unit 1, fifth street, the village, trafford park, manchester, m17 1jx –reg no: 06399133

Technical Specification cont.: Detection

Supply Voltage	21.6V - 26.4V DC
Current consumption	250mA @ 24V DC
Size	145W x 220H x 85D
Weight	1.7kg
Operating temperature range	-10 to +38°C (UL268) -10 to + 60°C (CEA4022)
Operating humidity range	0 – 90% non-condensing
Sensitivity range	0.03% to 25% obs/m
Detection principle	Laser light scattering mass detection and particle evaluation
Particle sensitivity range	0.003µm to 10µm
Dust discrimination principle	3D3 Laser Dust Discrimination (LDD)
Alarm levels	4 (Aux, Pre-alarm, Fire 1 and Fire 2)
Integral relays	Fire, Fault Relay Input PCB
Laser chamber service intervals	Greater than 10 years (dependent on environment)
Programming	Command Module or PC via RS232/RS485
Sampling pipe inlets	1
Exhaust air pipe outlets	1

Technical Specification: Extinguishant

Trade name	Novec1230
Chemical Name	1,1,1,2,2,4,5,5,5-Nonafloouro-4-(triflouromethyl)-3-pentanone
Environmental	Zero Ozone Depleting Potential 0.014 Atmospheric Lifetime (yrs).
Classifications Suitable for fire	Class A – Combustible Solids Class B – Flammable Liquids Class C – Flammable Gases Class E – Electrically Energised Fire Class F – Fats and Cooking Oils
Mechanism suppression	Physical
Firing Mechanism	Metron Electric Actuator
Nominal Pressire	16.5 Bar
Low Pressure Switch	12 Bar falling

Protect your business with Redetec...

putting fire protection where it counts.

19" rack-mount fire protection solutions

t: 0161 874 1942 - f: 0161 872 3282 – email: sales@redetec.co.uk – web: www.redetec.co.uk
registered office: unit 1, fifth street, the village, trafford park, manchester, m17 1jx –reg no: 06399133