

CableMaster 600

optimize!
softing



The CableMaster 600 is a professional cabling tester to test network, telephone and coax cabling. Equipped with a RJ45 jack for network cables and an F connector for coax cables, the CableMaster 600 verifies the wire map, determines the cable length and distance to the fault. The results can be saved and documented using the PC-based reporting software. The CableMaster 600 offers a multitude of functions for troubleshooting such as cable tracing, link detection up to 1Gb/s, PoE tests and port/outlet identification with ID remotes.

IT Networks



CABLING TESTER

<http://itnetworks.softing.com>

CableMaster 600

The CableMaster 600 is perfectly suited for professional installers and network operators who are challenged with testing network (RJ45) and coax cabling, verifying the correct wiring, determining cable lengths and documenting all this in test reports.

The CableMaster 600 professional cabling tester is highly versatile in usage - whether during installation, to verify which outlet is connected to the appropriate port in the patch panel, or after installation, for quality testing and documentation of the cabling, or for in-service trouble-shooting of the network.

The test results are displayed on the full-color graphic screen in a clear and easy to understand way, can be saved in the device.

Feature List

- Tests network and coaxial cables (RJ45 jack and F connector)
- Displays wire map in graphical format for rapid troubleshooting
- Determines cable length and distance to the cable fault performing a full TDR measurement
- High resolution color display for excellent readability in any environment
- Generation of test reports and documentation with PC-based reporting software
- Extensive test and fault finding capabilities such as:
 - Cable tracing / port identification using a tone probe - PoE detection and testing
 - Link test up to 1 Gb/s
 - Outlet/port identification with ID remotes

Cabling Tests

The CableMaster 600 features extensive test capabilities for RJ45 network, telephone and coaxial cable testing. Consisting of a main unit and a network/tel testing and ID remote, the CableMaster 600 is the ideal tool to test RJ45 cabling displaying the results in a wire map format. It verifies continuity, tests for reversals, miswires, split pairs, shorts, and opens. The cable length and the distance to the open will be determined using the integrated TDR (Time Domain Reflectometer).

The CableMaster 600 features an integrated tone generator to send a modulated audible signal into the cable which is detected by an optional tone probe used for cable tracing (unlabeled cables) and outlet/port identification. Cable ID remotes enable the user to identify which outlet is connected to the appropriate port in patch panel.



CABLING TESTER

Network Testing

The CableMaster 600 enables a rapid identification of network ports/outlets while displaying the link capability and the current link status. In addition, PoE (Power over Ethernet) presence is detected and displayed and can be tested with a load test compliant with IEEE 802.3 af/at.

Save and Report

Cable test results can be saved in the main unit and be exported to the PC via the included USB cable.

Included in the kit

CableMaster 600

Professional cable tester includes:
1 network/tel testing and ID remote
6xAA batteries
2 RJ45 cables
micro USB cable
pouch



CableMaster 650

Professional cable tester includes:
1 CableTracker CT15 tone probe
8 network/tel testing and ID remotes
1 cable assembly RJ45 to alligator clips, 1-20
coax ID remotes
6xAA batteries
9 RJ45 cables
micro USB cable
pouch



CableMaster 600

NORTH AMERICA & CANADA

Softing Inc.
Knoxville, Tennessee
Phone: +1.865.251.5252
E-mail: sales@softing.us

ASIA/PACIFIC

Singapore
Softing Singapore Pte. Ltd.
Singapore
Phone: +65-6569-6019
E-mail: asia-sales.itnetworks@softing.com

China

Softing Shanghai
Shanghai
Phone: +86-21-54133123
E-mail: china-sales.itnetworks@softing.com

EUROPE/MIDDLE EAST/AFRICA

Germany
Softing IT Networks GmbH
Haar, Munich
Phone: +49 89 45 656 660
E-mail: info.itnetworks@softing.com

France

Softing SARL
Créteil, Île-de-France
Phone: +33145172805
E-mail: info.france@softing.com

Italy

Softing Italia Srl.
Cesano Boscone, Milano
Phone: +39 02 4505171
E-mail: info@softingitalia.it

Austria

Buxbaum Automation GmbH
Eisenstadt
Phone: +43 2682 7045 60
E-mail: office@myautomation.at

For technical information and support please contact the Softing office in your country.

<http://itnetworks.softing.com>

For more information please contact:

©2017 Softing IT Networks. In line with our policy of continuous improvement and feature enhancement, product specifications are subject to change without notice. All rights reserved. Softing and the Softing Logo are trademarks or registered trademarks of Softing AG. All other trademarks, registered or unregistered, are sole property of their respective owners.

Parameter	Specifications
Measurement Technology	Time Domain Reflectometry (TDR)
Cable Measurements	Cable Testing and ID: up to 1,000 ft (305 m) Split Pair Detection: 3 ft (1 m) to 1,000 ft (305 m) Length Measurement: 0 to 1,500 ft (457 m), ± (5%+1 ft) Supports 8 continuity and ID numbers remotes (RJ 45) Supports 20 RJ 45 and 20 F connector ID only remotes
Power over Ethernet	Tests for IEEE 802.3af and IEEE 802.3at (PoE Plus) compliant PoE Tests for classes and loads cable up to 25.5 watts(at class 4 Identifies Mode A or B (pairs with PoE)
Active Ethernet	Indicates advertised speeds of 10/100/1000 base-t half or full duplex Can Link to network at 10/100 base-t
Maximum Voltage	Parameters refer to the maximum voltage that can be applied to any 2 connector pins without causing damage to the tester. - RJ Jack: 66 Vdc or 55 Vac - F-connector: 50 Vdc or Vac
Save Test Results	Stores up to 250 cable or network tests with user defined names
Tone Generation	Tone Frequencies: 730 Hz and 1440 Hz
Languages	English, French, German, Spanish
Battery Life	For 6xAA, 9VDC, 2,200 mA-hr (typical) alkaline battery: Operating - 20 hours typical Standby - 1.5 years typical (200 uA max standby current) Batteries are included
Altitude	10,000 ft (3048 m) operating
Temperature	Operating: 32 to 122°F (0 to 50°C) Storage: -22 to 140°F (-30 to 60°C)
Humidity	10 to 90% non-condensing
Enclosure	High-strength PC/ABS plastic with VO rating with boot Withstands 4 foot drop on to concrete
Size	1.85"H x 3.6"W x 6.8"L (4.7 x 9.15 x 17.3 cm)
Weight	With batteries: 1 lb 2 oz (510 g)
Safety Compliances	CE