

DRS - part number configuration

Standard Racks	Application	Width Depth	600				800				1000				Build	Sides	Colour	Base
			875	1000	1200	1400	875	1000	1200	1400	875	1000	1200	1400				
42 U racks																		
Basic	DB	42U	608	610	612	614	808	810	812	814	-	-	-	-	C	S	L	
Network	DN	42U	608	610	612	614	808	810	812	814	-	-	-	-	F	S	L	
Active	DA	42U	-	610	612	614	-	-	-	-	-	-	-	-	C	S	L	
Active+	DE	42U	-	610	612	614	-	-	-	-	-	-	-	-	C	S	L	
Switch	DS	42U	-	-	-	-	808	810	812	814	-	-	-	-	R	S	L	
Switch+	DP	42U	-	-	-	-	808	810	812	814	-	-	-	-	R	S	L	
Max	DM	42U	-	-	-	-	-	-	-	-	A08	A10	A12	A14	C	S	L	
Closed loop	DL	42U	-	-	612	614	-	-	812	814	-	-	-	-	C	S	L	
Cabling	DC	42U	-	-	-	-	808	810	812	814	-	-	-	-	C	S	L	
47U racks																		
Basic	DB	47U	608	610	612	614	808	810	812	814	-	-	-	-	C	S	L	
Network	DN	47U	608	610	612	614	808	810	812	814	-	-	-	-	F	S	L	
Active	DA	47U	-	610	612	614	-	-	-	-	-	-	-	-	C	S	L	
Active+	DE	47U	-	610	612	614	-	-	-	-	-	-	-	-	C	S	L	
Switch	DS	47U	-	-	-	-	808	810	812	814	-	-	-	-	R	S	L	
Switch+	DP	47U	-	-	-	-	808	810	812	814	-	-	-	-	R	S	L	
Max	DM	47U	-	-	-	-	-	-	-	-	A08	A10	A12	A14	C	S	L	
Closed loop	DL	47U	-	-	612	614	-	-	812	814	-	-	-	-	C	S	L	
Cabling	DC	47U	-	-	-	-	808	810	812	814	-	-	-	-	C	S	L	
52U racks																		
Basic	DB	52U	608	610	612	614	808	810	812	814	-	-	-	-	C	S	L	
Network	DN	52U	608	610	612	614	808	810	812	814	-	-	-	-	F	S	L	
Active	DA	52U	-	610	612	614	-	-	-	-	-	-	-	-	C	S	L	
Active+	DE	52U	-	610	612	614	-	-	-	-	-	-	-	-	C	S	L	
Switch	DS	52U	-	-	-	-	808	810	812	814	-	-	-	-	R	S	L	
Switch+	DP	52U	-	-	-	-	808	810	812	814	-	-	-	-	R	S	L	
Max	DM	52U	-	-	-	-	-	-	-	-	A08	A10	A12	A14	C	S	L	
Closed loop	DL	52U	-	-	612	614	-	-	812	814	-	-	-	-	C	S	L	
Cabling	DC	52U	-	-	-	-	808	810	812	814	-	-	-	-	C	S	L	

Example Order Code

DL 52 812 C S L

Type "U" Height Width Depth

Build	Sides	Colour	Base
C = Centre configuration assembled & palletised	S = With sides	B = Black	C = Jacking feet & castors
F = 4 post configuration assembled & palletised	N = Without sides	L = Grey	J = Jacking feet
R = Rear offset configuration assembled & palletised	L = LH side only		P = Plinth & jacking feet
	R = RH side only		Q = Option "P" + castors
			Blank = Nylon skids