

# Sirocco Tubing Accessories

Prysmian Part Number: See Individual Descriptions



## Sirocco Tube Connector 5 – 5mm

Part No. **XAGSC00462** or **XBFSC00075**

Used for simple push fit connection of 5mm to 5mm Sirocco tubing. Can be used in external plant and with internal Sirocco tubing of customer premises plant where gas sealing is not required.

Usage – 1 per tube connection. Pack of 10.



**XAGSC00462**



**XBFSC00075**

## Sirocco End Cap

Part No. **XAGSC00526** or **XBFSC00076**

Used for terminating unused Sirocco tubing within external plant.

Usage – 1 per unused tube. Pack of 10.



**XAGSC00526**



**XBFSC00076**

## Sirocco Water Blocking Connector

Part No. **XAPSC00531**

Used for water blocking Sirocco tubing entering underground external plant. A simple push fit device provides a water tight seal for tubes (unpopulated) and tubes with installed Sirocco units (populated). For populated tubing this device is fitted after Sirocco units have been installed.

Usage – 1 per populated or unpopulated tube. Pack of 10.



**XAPSC00531**

## Sirocco Gas Seal Connector 5 – 5mm

Part No. XAGSC00404 or XBFSC00075

Used for gas sealing Sirocco tubing entering a customers premises. The connector is used with OAsys Customer Premises Plant and provides the interface between external and internal Sirocco tubing. The connector simply push fits over the tube providing a gas tight seal for tubes (unpopulated) and tubes with installed Sirocco units (populated). The device allows fibre to be 'blown through' into the customer premises.

A sealing device is activated externally to seal the tube/unit.

Usage – 1 per external Sirocco tube. Pack of 10.



**XAGSC00462**



**XBFSC00075**

## Sirocco Tube Sealing Cap 5mm

Part No. XAGSC00406 or XBFSC00149

Used for sealing unused 5mm Sirocco tubing entering a customer premises. This cap is used with OAsys Customer Premises Plant and provides a gas tight seal to the unpopulated tubes.

Usage – 1 per unused external Sirocco tube. Pack of 10.



**XAGSC00406**



**XBFSC00149**

## OAsys Reducer Connector

Part No. XAGSC00408

Used for simple push fit connection of different sized Sirocco tubes e.g. 5mm 8mm. Can be used in external plant and with internal Blown Fibre tubing of customer premises plant where gas sealing is not required.

Usage – 1 per tube connection. Pack of 10.



**XAGSC00408**

Prysmian Telecom Cables & Systems UK Ltd, Chickenhall Lane, Bishopstoke, Hants SO50 6YU, UK

Technical Enquiries +44 (0) 2380 608760 Fax Number +44 (0) 2380 608769

© PRYSMIAN 2005. All Rights Reserved.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed correct at the time of issue. Prysmian reserves the right to amend this specification without notice. This specification is not contractually valid unless specifically authorised by Prysmian.

**Issue 01, October 2005**  
**Ref: SR015**